

B.E.G.**LUXOMAT[®]net**

PS-DALI-LINK-USB-REG

Prod.No. 93189 EAN: 4007529931897

- Voltage: 230 V AC -15/+10% 50 / 60 Hz
- Dimensions: 90 x 72 x 64 mm (4 TE)
- Settings: with Firmware update function button, B.E.G. PC Tools

Order data

Designation	Colour	Art.No
PS-DALI-LINK-USB-REG	white	93189

Technical data

Voltage:	230 V AC -15/+10% 50 / 60 Hz
Dimensions:	90 x 72 x 64 mm (4 TE)
Settings:	with Firmware update function button, B.E.G. PC Tools
Output voltage:	16 V DC
Power consumption:	6 W
Degree / class of protection:	IP20 / Class II
Ambient temperature:	+5 °C to +45 °C
Housing:	Polyamide, UV- resistant
Material color:	white
Connections and wires:	USB
Nominal current (max.):	210 mA

Product information

DALI power supply with integrated USB interface for DIN-rail mounting

For example, 45 DALI luminaires and 10 DALI-LINK control devices (multi-sensors or push-button interfaces) can be connected to the power supply.

Integrated USB interface allows expansion to networkable B.E.G. LUXOMAT®net DALI-SYS lighting management solution

Integrated LEDs for visualisation of operating information

Commissioning of the B.E.G. LUXOMAT®net DALI-LINK solution takes place via a free app and the PBM-DALI-LINK-4W-BLE push-button module

Suitable for: 93845, ...



