

B.E.G.**LUXOMAT[®]net**

RM1-LINK-REG DALI-2

Prod.No. 93083 EAN: 4007529930838

- Voltage: via DALI Bus, max. 22.5 V DC
- Dimensions: 85 x 18 x 63 mm (1 TE)
- Settings: PBM-DALI-LINK-4W-BLE + Smartphone with DALI-LINK App (iOS / Android)

Order data

Designation	Colour	Art.No
RM1-LINK-REG DALI-2	white	93083

Technical data

Voltage:	via DALI Bus, max. 22.5 V DC
Dimensions:	85 x 18 x 63 mm (1 TE)
Settings:	PBM-DALI-LINK-4W-BLE + Smartphone with DALI-LINK App (iOS / Android)
Typ. power input:	5 mA
Degree / class of protection:	IP20 / Class II
Ambient temperature:	-25 °C to +50 °C
Housing:	polycarbonate, UV-resistant
Material color:	white

Relay

Switching power:	3000 W, $\cos \varphi = 1$ 1500 VA, $\cos \varphi = 0.5$
Type of contact (k):	μ -contact, NO contact
Follow-up time:	1 min - 150 min (Cut-off and HVAC mode only)

Product information

DIN-rail DALI relay module with 1 switching channel

High-output and potential-free contact for loads with high inrush current

Integrated application controller with different operating modes

Operating modes: Standard, Cut-off, HVAC, Impulse, Alarm

Full range of functions can only be activated with other products of the product group B.E.G. LUXOMAT®net DALI-LINK



