

B.E.G. Feel comfortable in your building



THE NEW BASIC SENSORS

SAFE, COST-EFFECTIVE, FUNCTIONAL



Simple handling

Cost-effective variants

With essential functions



BASIC

PD2N-KNXs-BA-FC

Occupancy detector
Surface mounted
93533



PD2N-KNXs-BA-FM

Occupancy detector
Flush-mounted
93534



PD4N-KNXs-BA-FC

Occupancy detector
Surface mounted
93535



PD4N-KNXs-BA-FM

Occupancy detector
Flush-mounted
93536



New functions reduced to the essentials

Switching and control operation as well as settings for sensitivity adjustment can be carried out with the basic sensors. Functions such as KNX-Secure are also included in the basic version.

Cost-effective variants

Due to their reduced range of functions, the Basic sensors are cheaper to purchase and are therefore ideally suited for practical requirements.

Easy handling

By using optional accessories, the Basic sensors can be easily customised for different applications.

FUNCTION OVERVIEW OF SENSOR VARIANTS

	PD2N			PD4N		
	BA ¹	ST ²	DX ³	BA ¹	ST ²	DX ³
Number of light sensors	2	2	2	2	2	2
Number of motion sensors	1	1	1	4	4	4
Number of HVAC outputs	-	3	3	-	3	3
Sensitivity adjustment PIR	X	X	X	X	X	X
Bidirectional remote control	-	X	X	-	X	X
End customer remote control	-	-	X	-	-	X
Temperature sensor	-	-	X	-	-	X
Noise sensor	-	-	X	-	-	X
Logic module	-	-	X	-	-	X
Presence simulation	-	-	X	-	-	X
Internal buttons	-	-	-	-	-	-
Internal orientation light	-	-	-	-	-	-
Slave output	X	X	X	X	X	X
Slave input	X	X	X	X	X	X
Switching mode	X	X	X	X	X	X
Control mode	X	X	X	X	X	X
Semi-automatic/fully automatic	X	X	X	X	X	X
Light scenes	-	X	X	-	X	X
Offset mode	-	X	X	-	X	X
Orientation light function	-	X	X	-	X	X
Burn-in function	-	X	X	-	X	X
Parameter changes via object	X	X	X	X	X	X
Self-adjustment of run-on time	-	X	X	-	X	X
Short presence	-	X	X	-	X	X
Direction recognition	-	-	-	-	X	X
Daylight-dependent switch-off	X	X	X	X	X	X
HCL/ RGB control	-	-	X	-	-	X
KNX Secure	X	X	X	X	X	X



For further info:

¹Basic – Economic solution for simple requirements

²Standard – comprehensive solution for common requirements

³Deluxe – premium solution for demanding applications

STANDARD

DELUXE

PD2N-KNXs-ST 93511



PD2N-KNXs-OCCULOG-DX 93531



PD2N-KNXs-OCCULOG-DX 93530



PD2N-KNXs-ST 93510



PD2N-KNXs-DX 93513



PD2N-KNXs-DX 93512



PD4N-KNXs-ST 93515



PD4N-KNXs-DX 93517



PD4N-KNXs-DX 93516




PD4N-KNXs-ST 93514



PD11-KNXs-FLAT-DX 93523



Indoor 180-KNXs-DX 93525



PD11-KNXs-FLAT-ST 93522



PD9-KNXs-DX 93520



PD9-KNXs-GH-DX 93521



Indoor 180-KNXs-ST 93524



PD4-KNXs-GH-DX 93518



PICO-KNXs-DX 93529



PICO-KNXs-ST 93539



RC-plus next N 230 KNXs-DX 93527



RC-plus next N 230 KNXs-DX 93528



PD2N-RF-KNXs-DX 93580



Accessories in various colours
and available for other installation methods.
Details at www.beg-luxomat.com

Are you interested?
Then simply contact us:
projects@beg.de

